



Media converter 10/100 Mbps.
From Copper (RJ45) to Optical Fibre (ST or SC)

Wide range of media converters, from copper to optical fibre at 10/100 Mbps. And with a variety of connectors (SC or ST) and distances of up to 20 km.

Standards:

IEEE 802.3 10BASE-T.

IEEE 802.3u 100BaseTX y 100BaseFX

Ports:

1 TX port.

1 FX port.

Speed:

10BaseT: 10/20 Mbps in half/full duplex.

100BaseTX/FX: 100/200Mbps in half/full duplex.

Switching Method: Store-and-Forward.

Transmission Rate: 14,880/148,800pps in 10/100Mbps.

LED's: Per Unit: (2 Led's): TX LNK/ACT; FX LNK/ACT.

Dimensions: 54.6 + 80.3 + 22.1 mm.

Weight: 0.14kg.

External Power Supply: 12VDC, 0.8A.

Consumption: 9.6W Max.

Temperature during functioning: 0°C ~ 50°C - (32°F ~ 122°F).

Temperature in storeroom: -25°C ~ 70°C (-13°F ~ 158°F).

Humidity: 10 ~ 90%, without condensation.

Certificates: FCC part 15 Class A, CE.

Models:

OV-11T: Mini 10/100TX to 100FX (ST)

OV-11C: Mini 10/100TX to 100FX (SC)

OV-11C-20: Mini 10/100TX to 100FX (SC). 20 Km.

OV-11C-20: Mini 10/100TX to 100FX (SC). 20 Km.

